

DEPARTMENT OF CONSUMER AND INDUSTRY SERVICES

DIRECTOR'S OFFICE

GENERAL INDUSTRY SAFETY STANDARDS

Filed with the Secretary of State on November 1, 1974 (as amended December 1, 1983)

These rules take effect 15 days after filing with the Secretary of State

(By authority conferred on the director of the department of consumer and industry services by sections 16 and 21 of Act No. 154 of the Public Acts of 1974, as amended, and Executive Reorganization Order No. 1996-2, being §§408.1016, 408.1021, and 445.2001 of the Michigan Compiled Laws)

R 408.15411, R 408.15413, R 408.15415, R 408.15416, R 408.15422, R 408.15429, R 408.15452, and R 408.15461 of the Michigan Administrative Code, appearing on pages 3850 to 3854 and 3856 of the 1979 Michigan Administrative Code, are amended to read as hereinafter set forth.

R 408.15421, R 408.15423, R 408.15424, R 408.15425, and R 408.15431 of the Michigan Administrative Code, appearing on pages 3852 to 3855 of the 1979 Michigan Administrative code, are rescinded.

Bureau of Safety and Regulation, Standards Division Web-Site: www.cis.state.mi.us/bsr/divisions/std

PART 54. POWERED GROUNDSKEEPING EQUIPMENT

TABLE OF CONTENTS

Scope.....	R 408.15401	Construction, snow throwers, general	R 408.15426
Definitions; A to E	R 408.15403	Construction, walk behind snow throwers	R 408.15427
Definitions; F to P.....	R 408.15404	Construction, riding snow throwers	R 408.15428
Definitions; R and S	R 408.15405	Controls, self-propelled snow throwers	R 408.15429
Definitions; T to W.....	R 408.15406	Operating rules, walk behind mowers	R 408.15442
Employer responsibility.....	R 408.15411	Operating rules, riding vehicles	R 408.15443
Employee responsibilities	R 408.15412	Operating rules, snow throwers	R 408.15444
Personal protective equipment	R 408.15413	Shredder baggers and compost mills.....	R 408.15451
Lubrication and maintenance	R 408.15414	Edger-trimmer	R 408.15452
Labeling	R 408.15415	Rotary tillers	R 408.15461
Operating rules generally	R 408.15416		
Construction; powered mowers; lawn and garden tractors	R 408.15422		

GENERAL PROVISIONS

R 408.15401. Scope.

Rule 5401. This part provides rules for the construction, the maintenance and the safe operation of powered groundskeeping and related equipment and attachments by the employer and their safe use by the employee in, around or about a place of employment.

R 408.15403. Definitions; A to E.

Rule 5403. (1) "Attachment" means detachable equipment, such as, but not limited to, a mower, snow thrower, tiller or sweeper designed for use with a propulsion vehicle.

(2) "Blade enclosure" means the guard around the periphery of the rotary mower blade.

(3) "Braking distance" means the distance traveled between the point of first application of the brake to the point at which the vehicle comes to rest.

(4) "Discharge guide" means the device which directs the snow from the impeller to the deposit area, and which is rotatable to deliver the snow in the desired direction.

(5) "Edger-trimmer" means a walk behind powered machine with a rotary blade designed to edge grass in a vertical position and trim grass when adjusted to a horizontal position.

R 408.15404. Definitions; F to P.

Rule 5404. (1) "Foot protection" means footwear such as, but not limited to, safety shoes or strap-on foot guards.

(2) "Grass catcher" means a part or a combination of parts which provides a means for collecting grass clippings and other debris.

(3) "Groundskeeping equipment" means that equipment such as, but not limited to, lawn mowers, lawn and garden tractors, leaf blowers, snow throwers, shredders, compost mills and tillers used to maintain lawns, gardens, walks and drives.

(4) "Impeller" means a final power driven device which imparts energy to discharge the snow.

(5) "Power reel mower" means a grass cutting machine which uses a power source to rotate 1 or more helically formed blades about a horizontal axis to provide a shearing action with a stationary cutter bar.

(6) "Power rotary mower" means a grass cutting machine which uses a power source to rotate 1 or more blades about a vertical axis.

R 408.15405. Definitions; R and S.

Rule 5405. (1) "Riding garden tractor" means a self-propelled riding vehicle designed for general purpose lawn and garden work by use of attachments and which produces less than 1500 pounds but more than 500 pounds of draw bar pull.

(2) "Riding lawn tractor" means a self-propelled riding vehicle designed for general purpose lawn work by use of separate attachment.

(3) "Riding mower" means a self-propelled riding vehicle designed specifically for cutting grass.

(4) "Rotary tiller" means a powered machine with steel tines attached to a horizontal shaft which revolves to till soil.

(5) "Shredder bagger" means a machine with a rotating device which breaks up debris such as leaves, twigs and small branches and packs it into a catcher or bag.

(6) "Single stage snow thrower" means a snow thrower which incorporates the impeller into the collector either at the end of the collector or in the middle.

(7) "Snow thrower" means a machine designed to move snow from 1 area to another.

(8) "Snow thrower collector" means an auger or similar device used to collect snow.

R 408.15406. Definitions T to W.

Rule 5406. (1) "Tip speed" means the distance a rotary blade tip covers in 1 minute, or circumference in feet times revolution during a 1 minute interval.

(2) "Two stage snow thrower" means a snow thrower with the impeller as a separate unit from the collector.

(3) "Walk behind mower" means a grass cutting machine either pushed or self-propelled, controlled by an operator walking behind the unit.

(4) "Walk behind snow thrower" means a snow thrower either pushed or self-propelled, controlled by an operator walking behind the unit.

R 408.15411. Employer responsibility.

Rule 5411. An employer shall:

- (a) Provide training to an operator of powered groundskeeping and related equipment regarding the operating procedures, hazards, and safeguards to the assigned job.
- (b) Provide personal protective equipment necessary to protect the employee from the recognized hazards of the equipment as prescribed in Part 33. Personal Protective Equipment, being R 408.13301 et seq. of the Michigan Administrative Code, and require its use.
- (c) Not allow powered groundskeeping and related equipment to be operated which is not guarded as prescribed by this part, or which has a known defect that could affect the safety of the operator.
- (d) Not allow powered groundskeeping equipment and attachments to be used for operations other than those for which the equipment was designed.

R 408.15412. Employee responsibilities.

Rule 5412. An employee shall:

- (a) Use personal protective equipment required by this part.
- (b) Report to their supervisor any equipment or safeguard which is found defective.
- (c) Not operate, lubricate or provide maintenance of any equipment until trained in the operation, lubrication, maintenance procedures, hazards and safeguards and has been authorized to do so.
- (d) Not remove a guard except for authorized maintenance purposes. The guard shall be replaced before the machine is returned to operation.

R 408.15413. Personal protective equipment.

Rule 5413. (1) An operator of powered groundskeeping equipment subjected to a noise level in excess of that established by the division of occupational health, shall be provided with hearing protection prescribed by rule 6260 of the occupational health standards of the division of occupational health.

(2) When operating powered groundskeeping equipment an operator shall be provided with and use eye protection in accordance with, and as prescribed in, Part 33. Personal Protective Equipment, being R 408.13301 et seq. of the Michigan Administrative Code.

(3) An operator of a walk behind power rotary mower shall not wear open toed or canvas-type shoes.

(4) An operator of a power rotary mower shall be provided with and use foot protection as prescribed in Part 33. Personal Protective

Equipment, being R 408.13301 et seq. of the Michigan Administrative Code.

R 408.15414. Lubrication and maintenance.

Rule 5414. Equipment covered by this part shall be shut off or disconnected during lubrication and maintenance, except when it is necessary to make adjustments with the power on.

R 408.15415. Labeling.

Rule 5415. (1) All positions of an operating control shall be legibly identified by durable labels.

(2) Self-propelled groundskeeping equipment shall have a durable label at the engine starting control point with the wording, or similar wording, "Caution. Be sure the operating control is in neutral before starting engine."

(3) A walk-behind or riding rotary mower shall have labeled warning instructions at or near the discharge opening stating, "Caution. Mower shall not be used unless the opening guard or grass catcher is in place."

(4) A riding mower shall have a durable label installed in a place where the operator can readily see it stating, "Caution:

- (a) Keep all guards and shields in place.
- (b) Before leaving the operator's position, shift the transmission to neutral, set parking brake and disengage attachment clutch.
- (c) Wait for all movement to stop before servicing machine."
- (5) A snow thrower shall have a labeled warning instruction on the discharge guide stating, "Warning — Keep hands out of discharge guide while engine is running."
- (6) A labeled warning instruction "Caution — Keep hands and feet clear of collector while engine is running" shall be placed on the collector housing of a snow thrower.
- (7) All warning labels shall be maintained in a legible and readable condition.

R 408.15416. Operating rules generally.

Rule 5416. (1) A gas tank shall not be filled:

- (a) Indoors, except in an area conforming to the requirements of the state fire marshal rules entitled "Flammable Liquids," being R 28.601 to R 28.739 of the Michigan Administrative Code.
- (b) While the engine is running.
- (c) While a source of ignition is present in the immediate area.
- (2) A portable container used for refueling shall be an approved safety can with an automatic closing cap and flame arrester.
- (3) Spills of gasoline which could create a hazard shall be cleaned up immediately.
- (4) The drive mechanism of self-propelled groundskeeping equipment shall be disengaged before starting a motor or engine.
- (5) An engine or motor governor adjustment shall not be made or changed to create an overspeed condition.
- (6) An engine or motor shall be stopped and an inspection made after striking a foreign object with a machine or if a vibration develops.
- (7) An engine or motor shall be stopped when clearing a clog or a jam or when removing an attachment.
- (8) An area to be mowed shall be checked and cleared of any object which might be picked up and thrown by the blade.
- (9) The discharge of material shall not be directed at another person.

(10) Groundskeeping equipment shall not be left running, unattended, if the operator is beyond vision or more than 25 feet away from the equipment.

(11) Groundskeeping equipment, without approved double insulation and powered by 110 volts or more, shall be connected to a grounded service outlet. Unless equipment is an approved double insulated device, its cord and any extension cords shall be of 3-wire grounded type and of a contrasting color to the foliage such as, but not limited to, orange or yellow.

(12) All rotating shafts, fly wheels, chains, belts, pulleys, and sprockets, shall be located or guarded to prevent accidental contact

in accordance with and as prescribed in, Part 7. Guards for Power Transmission, being R 408.10701 to R 408.10765 of the Michigan Administrative Code.

R 408.15421. Rescinded.

SPECIFIC PROVISIONS

R 408.15422. Construction; powered mowers; lawn and garden tractors.

Rule 5422. A new powered lawn mower, lawn tractor, or a garden tractor and its attachments, purchased after the effective date of this part, shall meet the requirements of ANSI B 71.1-1972 standard, "Safety Specifications for Power Lawn Tractors," which is incorporated herein by reference, and shall bear a permanently attached tag or label so indicating. This standard is available for inspection at the Lansing office of the department of consumer and industry services and may be purchased from the American National Standards Institute, 1430 Broadway, New York, New York 10018, or from the Michigan Department of Consumer and Industry Services, 7150 Harris Drive, Box 30643, Lansing, Michigan 48909, at a cost of \$4.50 each.

R 408.15423. – R 408.15425. Rescinded.

R 408.15426. Construction, snow throwers, general.

Rule 5426. (1) The speed of the collector shall be not more than the manufacturer's rated speed.

(2) The impeller of a 2-stage snow thrower shall be not more than the manufacturer's rated speed.

(3) A snow thrower collector housing shall extend to the front of the auger travel path on both sides.

(4) The collector shall incorporate a shear bolt or slip clutch protection against a blockage of the collector.

(5) The discharge guide rotating mechanism shall not be capable of delivering snow to the operator's area.

R 408.15427. Construction, walk behind snow throwers.

Rule 5427. (1) A handle for a walk behind snow thrower shall be secured to the snowthrower to prevent unintentional uncoupling.

(2) A positive upper limit stop or latch shall be provided for the handle of a walk behind snow thrower at the upper normal position.

R 408.15428. Construction, riding snow throwers.

Rule 5428. (1) A riding snow thrower shall be provided with stops to prevent locking of the steering mechanism.

(2) The snow thrower controls shall be accessible to the operator from the operator's control position.

(3) A snow thrower shall have adjustable skid shoes or gauge wheels to control operating height.

R 408.15429. Controls; self-propelled snow throwers.

Rule 5429. (1) The traction drive directional control lever, when provided on a self-propelled snow thrower, shall be moved forward to cause the machine to move forward and rearward to move in reverse.

(2) The throttle control of a self-propelled snow thrower, if separate from the directional control, shall be moved forward or upward to increase speed and rearward or downward to decrease speed.

R 408.15431. Rescinded.

R 408.15442. Operating rules, walk behind mowers.

Rule 5442. (1) A walk behind mower shall be moved across the face of a slope of more than 17 degrees, never up and down, except by use of a rope to raise and lower the mower while standing at the top of the slope.

(2) An electric powered walk behind mower shall be shut off and disconnected from the electrical source when cleaning, repairing or adjusting.

(3) The operator shall maintain direct control of a self-propelled, walk behind mower. The operator shall adjust the ground speed to their gait for proper control.

R 408.15443. Operating rules, riding vehicles.

Rule 5443. (1) A riding vehicle shall not carry a passenger other than the operator.

(2) The source of power to an attachment of a riding vehicle shall be disengaged when the attachment is not in use or is being transported.

(3) When a riding vehicle is left unattended, the steps listed in subdivision (b) of subrule (4) of rule 5415 shall be followed.

(4) Riding groundskeeping equipment shall not be operated up or down a slope of more than 26 degrees or move across the face of a slope of more than 17 degrees.

(5) A deviation from the requirements of subrule (4) may be obtained from the department of consumer and industry services by presenting special design or modification criteria which shows an ability to perform safely on a specific slope of a greater degree without slipping or tipping.

R 408.15444. Operating rules, snow throwers.

Rule 5444. (1) When necessary to operate a snow thrower over graveled areas, the snow thrower shall be placed in its highest operating position.

(2) An area to be cleared of snow shall be checked and cleared of any visible object that might stop the collector or be picked up and then thrown by the impeller.

(3) The collector clutch shall be disengaged when adjusting the deflector guide upwards and downward.

(4) An employee shall not attempt to clear the discharge guide with the engine running.

(5) An operator shall maintain direct control of a self-propelled walk behind snow thrower. The operator shall adjust ground speed to their gait for control.

R 408.15451. Shredder baggers and compost mills.

Rule 5451. (1) The power of a shredder bagger or compost mill shall be shut off and all motion stopped before moving it.

(2) A clog or a jam in a shredder bagger or compost mill shall not be cleared until the power has been shut off and all motion stopped.

(3) The hopper feed opening of a shredder bagger or compost mill shall be of such distance from the cutting knives or impeller so that an operator cannot make contact or a guarding means shall be employed. A baffle gate shall be installed at the feed opening of a hopper to reduce hazard of kick backs.

(4) The discharge opening shall be covered by a guard, container or catcher whenever the shredder bagger or compost mill is under power.

R 408.15452. Edger-trimmer.

Rule 5452. (1) The cutting blade of an edger-trimmer shall be covered with a guard to prevent foreign objects from being discharged into the operator's area or at an angle above 15 degrees from the ground.

(2) The power shall be shut off when converting from edging to trimming operation or from trimming to edging.

R 408.15461. Rotary tillers.

Rule 5461. (1) Rocks or other entanglement shall not be removed from the tines until the power has been shut off and all motion stopped.

(2) The tine area shall be operated or shielded in such a manner as to prevent debris or other missiles from being thrown.

(3) An operator shall maintain direct control of the rotary tiller. The operator shall adjust the ground speed to their gait for control.